

Sole Verde

450W Mono Bifacial

450 W · 53.6V Voc

Mono bifacial double-glass module — 156 half-cut cells, 2.0mm tempered glass both sides, IP68 junction box.

SPECIFICATIONS

Imp	9.94A
Isc	10.46A
Vmp	45.28V
Voc	53.58V
Cells	156 half-cut (6×26) mono
Glass	2.0mm / 2.0mm double glass
source	Soleverde Catalogue 2026 v2
Connector	Genuine MC4-EV02 · IP68 · 3 diodes
Dimensions	2198 × 1005 × 35 mm · 29.0kg
Efficiency	20.4%
Rated power (Pmax)	450W (0~+5W)
Temp. coefficient Pmax	-0.354%/°C



Enquire on WhatsApp

[+971529741660](https://www.whatsapp.com/chat?phone=971529741660)["https://soleverde-backoffice-production.up.railway.app/VAPID_PUBLIC_KEY=BDSCdM_pCHlQGbjEwtd0YnGm2WQc1pwcsn_6Vw9"](https://soleverde-backoffice-production.up.railway.app/VAPID_PUBLIC_KEY=BDSCdM_pCHlQGbjEwtd0YnGm2WQc1pwcsn_6Vw9)

Specifications subject to change without notice. Full warranty terms ship with the product.

